



**045-1462-000**

## Art. 045-1462-000

### Exhausted oil drain unit 65 l

Tank capacity 65 l with level indicator

Abs tool holder basin with 3 sections


Recovery basin capacity 15 l

with breakwater grate to drip the substituted oil filters

Pneumatic air emptying (max pressure 0,5 bar)



045-1462-000	26,900	0,220	1
--------------	--------	-------	---



**045-1460-000**

## Art. 045-1460-000

### Exhausted oil drain unit 90 l

Tank capacity 90 l with level indicator

Abs tool holder basin with 3 sections

Recovery basin capacity 20 l

with ergonomic and **360° swivelling** abs funnel

with breakwater grate to drip the substituted oil filters

Pneumatic air emptying (max pressure 0,5 bar)

## Art. 045-1460-E00


### Exhausted oil drain unit 90 l

Composed like Art.045-1460-000 but with:

Recovery basin capacity 15 l



045-1460-000	33,500	0,240	2
045-1460-E00	29,500	0,240	1



**045-1465-000**

## Art. 045-1465-000

### Exhausted oil drain unit 120 l

Tank capacity 120 l with level indicator

Abs tool holder basin with 3 sections

Recovery basin capacity 20 l


with ergonomic and **360° swivelling** abs funnel

with breakwater grate to drip the substituted oil filters

Pneumatic air emptying (max pressure 0,5 bar)



045-1465-000	33,800	0,310	2
--------------	--------	-------	---



Technical data		045-1462-000	045-1460-000	045-1460-E00	045-1465-000
Basin dimensions	mm	ø 450	760X705	ø 450	760X705
Minimum height	mm	1000	1200	1200	1200
Maximum height	mm	1700	1850	1850	1850
Emptying hose length	mm	2	2	2	2

For the recovery by fall of exhausted oil of the engine, the transmission and the differential of motor-vehicles on lifts.

The basin is equipped with a grate of support to drip the substituted filters, and it can be regulated according to the height.

**Warning:** It is not possible to recovery brake oils, fuels, inflammable and corrosive liquids.